| | NPH NPH |
|--------|--|
| | Heater Order Form call toll free: 1.877.674.9744 |
| | CUSTOMER INFORMATION:: Please choose one and fill-in & mark appropriate box. |
| | |
| | Company: Date: Order Priority: |
| | Regular Rush* |
| | Ordered By: P.O.: |
| | Encl. Drw No: |
| | Phone: () Ship via: |
| | □ Pick-up □ Courier □ C.O.D. |
| | Fax: (Rush*/Direct Courier Customer's a/c: * Rush charges may apply. |
| | |
| | HEATER TYPE: Please choose one and fill-in the dimensions. |
| | CTDID HEATERS |
| | STRIP HEATERS |
| | CONSTRUCTION TYPE: Leads exit from top sheet Leads exit from side/end |
| | |
| | Length Width <u>UNIT :</u> Inch mm |
| | FLECTRICAL SPECIFICATIONS: Please choose one and fill in the wattage as per construction |
| | Flease choose one and fill-in the wattage as per construction. |
| | Voltage: |
| | <u>ronager</u> watts |
| | ELECTRICAL TERMINATION STYLES: Please choose a Style. |
| | |
| | Lead Wire Terminals Exiting Through the Top Sheet |
| | |
| | GM Style E Style H Style K Style G Style A Style B1 Style B2 Style |
| | (See pages 5 & + for details) |
| | Lead Wire Terminals Exiting from the Side or the End |
| | Lead Wife Ferminals Exiting from the state of the End |
| | L / LF Styles J / JF Styles |
| | |
| | LEADS TYPE & LENGHT: choose one and fill-in the length. |
| | |
| | Stainless Steel Braid: Length or Armor Cable: Length Length |
| | |
| | OPTIONS: SPECIAL INSTRUCTIONS: |
| | ST HONS. |
| | Built-in T/C ** |
| | Cuts/Slots/Holes** |
| | ☐ GND |
| _ _ | Pre-wired Euro-Box |
| | |
| | ** Drawing or Sketch Required. Please Enclose. |



National Plastic Heater Sensor & Control Co.

phone: 416.491.8436 toll free: 1.877.674.9744 fax: 416.491.2433 Toronto, Ontario Canada e-mail: sales@nphheaters.com website www.nphheaters.com